

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1508-319

AMENDMENTS TO THE CLAIMS

Please add new claims 34-39 as set forth below.

1. (Originally Presented) A variable trajectory sprinkler nozzle assembly comprising:

a nozzle support structure;

a nozzle body pivotally mounted within said nozzle support structure; and

a trajectory adjuster operatively connected to said nozzle body such that movement of said trajectory adjuster causes pivotal movement of said nozzle body;

at least one secondary opening positioned adjacent said nozzle body on said nozzle support structure.

2. (Originally Presented) A nozzle assembly according to claim 1, wherein said at least one secondary opening is pivotally mounted on said support structure.

3. (Originally Presented) A nozzle assembly according to claim 1, wherein said at least one secondary opening contains a nozzle having a pre-set trajectory.

4. (Originally Presented) variable trajectory sprinkler nozzle assembly comprising:

a nozzle support structure;

a nozzle body pivotally mounted within said nozzle support structure; and

a trajectory adjuster operatively connected to said nozzle body such that movement of said trajectory adjuster causes pivotal movement of said nozzle body; and,

a break-up screw positioned on said nozzle support structure so as to break-up a throw-path of water at a predetermined angle of said nozzle body.

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1506-319

5. (Originally Presented) A nozzle assembly according to claim 4, wherein said break-up screw is disposed on said nozzle support structure to extend upwardly from a lower surface of said nozzle support structure into a stream path of said nozzle body.
6. (Originally Presented) A nozzle assembly according to claim 4, wherein said break-up screw is adjustable.
7. (Originally Presented) A sprinkler bypass system comprising:
 - a sprinkler inlet;
 - a stator positioned proximal to said inlet;
 - said stator including a plurality of pivotable surfaces disposed thereon;
 - a bypass stop positioned above said stator and biased downwardly against said stator; and,
 - said pivotable surfaces sized and shaped to pivot upwardly from said stator against said bypass stop when flow through said inlet and against said stator exceeds a predetermined amount.
8. (Originally Presented) A sprinkler bypass system according to claim 7, wherein pivotable surfaces are connected to said stator with a living hinge.
9. (Originally Presented) A sprinkler bypass system according to claim 7, wherein said surfaces are comprised of reeds.
10. (Originally Presented) A sprinkler bypass system according to claim 9, wherein said plurality of reeds includes 6 reeds placed circumferentially around said stator.
11. (Originally Presented) A reversible sprinkler device comprising:
 - an inlet;
 - a turbine located proximal to said inlet;
 - a planetary gear drive operatively connected to said turbine such that

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1508-319

rotation of said turbine causes rotation of said planetary gear drive;

a reversible gear train interposed between said turbine and said planetary gear drive, said reversible gear train being movable between two states, each state corresponding to one rotational direction of said planetary gear; and,

said turbine being a unidirectional turbine.

12. (Originally Presented) A reversible sprinkler device according to claim 11, wherein said reversible gear train includes two groups of pinion gears, one group for rotating said planet gear in a first direction and a second group for rotating said planet gear in an opposite direction.

13. (Originally Presented) A reversible sprinkler device according to claim 12, wherein said reversible gear train includes a spur gear that drives both groups of pinion gears.

14. (Originally Presented) A reversible sprinkler device according to claim 13, wherein said reversible gear train includes a cluster gear which is selectively engageable with one of said groups of pinion gears according to said state of said reversible gear train.

15. (Originally Presented) A reversible sprinkler device according to claim 11, further comprising a reverse rotation actuating mechanism connected to said reversible gear train.

16. (Originally Presented) A reversible sprinkler device comprising:

an inlet;

a turbine located proximal to said inlet;

a flow director interposed between said inlet and said turbine;

a planetary gear drive operatively connect to said turbine such that rotation of said turbine causes rotation of said planetary gear;

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1506-319

said flow director being movable between two states, each state corresponding to one rotational direction of said planetary gear;

said flow director being biased into either one of said two states by an overcenter spring assembly;

said overcenter spring assembly including a trip arm and a pivot post and a over center spring; said overcenter spring positioned in a loaded stated between said trip arm and said pivot post and said overcenter spring traversing a center hole of said low director; and,

said turbine being a bidirectional turbine.

17. (Originally Presented) A sprinkler system comprising:

an upper sprinkler assembly;

a lower sprinkler assembly;

a seal located between said upper sprinkler assembly and said lower sprinkler assembly;

a clutch mechanism for allowing manual relative rotation of said upper sprinkler assembly relative to said lower sprinkler assembly;

said clutch mechanism located spatially above said seal.

18. (Originally Presented) A sprinkler system according to claim 17, wherein said clutch mechanism includes a connective structure connecting said upper sprinkler assembly and said lower assembly, wherein said connective structure is fixedly connected to said lower sprinkler assembly and in movable connection with said upper sprinkler assembly.

19. (Originally Presented) A sprinkler system according to claim 18, wherein said movable connection of said connective structure includes a resilient sealing connection.

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1506-319

20. (Originally Presented) A sprinkler system according to claim 19, wherein said resilient sealing connection is an o-ring connection.

21. (Originally Presented) A sprinkler system according to claim 19, wherein said movable connection further includes a friction member interposed between said resilient sealing connection and said upper sprinkler assembly.

22. (Originally Presented) A sprinkler system according to claim 21, wherein said friction member comprises a Teflon ring disposed around an internal circumference of said upper sprinkler assembly.

23. (Originally Presented) An adjustable arc sprinkler mechanism comprising:
an upper rotatable sprinkler housing;
a lower stationary sprinkler housing;

an arc stop assembly interposed between said upper and lower sprinkler housing;

said arc stop assembly including an angularly fixed arc stop member and an angularly movable arc stop member; and,

wherein at least one position of said angularly movable arc stop enables said rotatable sprinkler housing to rotate in one continuous direction.

24. (Originally Presented) An adjustable arc sprinkler mechanism according to claim 23, wherein said angularly movable arc stop is movable according to disengagement of said arc stop assembly from said upper rotatable sprinkler housing.

25. (Originally Presented) An adjustable arc sprinkler mechanism according to claim 24, wherein said disengagement of said arc stop is through radial movement of said arc stop assembly.

26. (Originally Presented) An adjustable arc sprinkler mechanism according to claim 23, wherein said fixed arc stop member includes a radially flexible stop

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1506-319

surface, said stop surface being radially flexed out of engagement with a sprinkler stop when said upper rotatable sprinkler housing with said fixed arc stop member is moving in a full circle direction.

27. (Originally Presented) An arc limit system for a sprinkler comprising:
- an upper rotatable sprinkler housing;
 - a lower stationary sprinkler housing;
 - an actuator mechanism operable to control a rotational direction of said upper housing;
 - said actuator mechanism having a trip member;
 - a plurality of trip stops disposed on said lower housing and positioned on either side of said trip member so as to engage said trip member upon manual rotation of said upper rotatable sprinkler housing.

28. (Originally Presented) An arc limit system according to claim 27, wherein said trip stops are positioned to prevent excessive force from being transmitted from said trip member to a drive train of said sprinkler.

29. (Originally Presented) A riser assembly for a sprinkler comprising:
- a riser housing having a compartment for receiving a sprinkler riser;
 - a top surface disposed on said sprinkler riser;
 - said top surface sized to fit and cover a top opening of said compartment;
 - a snap ring insertable into said compartment for retaining said sprinkler riser in said riser housing;
 - said top surface having a plurality of ribs disposed on a bottom surface of said top cap; and,
 - said ribs being radially contoured along said bottom surface so as to contact and urge movement of said snap ring into said compartment during

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1506-319

installation of said snap ring.

30. (Originally Presented) A riser assembly according to claim 29, wherein said plurality of ribs include a first angled surface and said compartment includes a second angled surface at a top region of said compartment, and wherein said first angled surface and said second angled surface are configured to ensure the formation of a space for containing said snap ring, said space increasing in size in a direction into said compartment.

31. (Originally Presented) A riser assembly according to claim 30, wherein an angle between said first angled surface and said second angled surface is approximately 7 degrees.

32. (Originally Presented) A riser assembly according to claim 29, wherein said top surface is sized such that said top surface properly mates with said riser housing only upon complete insertion of said snap ring.

33. (Originally Presented) A sprinkler comprising:

a riser housing;

a sprinkler riser movable upwardly and downwardly within said riser housing;

a pilot valve connected to said riser housing;

said pilot valve being movable between a state to allow water flow into said sprinkler riser and a state terminating the flow of water into said sprinkler riser;

said pilot valve including a pressure regulating mechanism; and,

said pressure regulating being adjustable according to a desired threshold pressure regulating value;

a visual indicia of said threshold pressure regulating value being disposed on an external surface of said pilot valve.

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1506-319

34. (Newly Presented) An adjustable arc sprinkler mechanism comprising:
a sprinkler housing having a rotating portion, a stationary portion and an arc adjustment mechanism;

said arc adjustment mechanism including an arc stop selectively angularly movable relative to said rotating portion and said stationary portion so as to set a desired arc for said rotating portion of said sprinkler mechanism;

said arc stop being movable between a minimum arc setting and a full circle setting;

said arc stop being movable between said minimum arc setting and said full circle setting without changing a vertical height of said sprinkler mechanism.

35. (Newly Presented) An adjustable arc sprinkler mechanism according to claim 34, wherein said arc stop is movable according to disengagement of an arc stop assembly from said rotatable portion.

36. (Newly Presented) An adjustable arc sprinkler mechanism according to claim 34, wherein said arc adjustment mechanism further includes a fixed arc stop member disposed on said rotating portion, wherein said fixed arc stop member includes a radially flexible stop surface, said stop surface being radially flexed out of engagement with a sprinkler stop when said arc stop is at said full circle setting.

37. (Newly Presented) An adjustable arc sprinkler mechanism according to claim 34, wherein said arc stop is positioned outside the path of a direction trip mechanism when said arc stop is located at said full circle setting.

38. (Newly Presented) A method of establishing full circle operation of an adjustable arc sprinkler mechanism comprising:

providing a sprinkler having a rotating section, a stationary section and an

Applicant: Santiago et al.
Serial No.: 10/774,705
Group Art Unit: 3752

PATENT
Docket No.: 1506-319

arc adjustment section, wherein said sprinkler has an established sprinkler height;

disengaging said arc adjustment section from said rotating section without changing the overall height of said adjustable arc sprinkler mechanism;

moving said arc adjustment section to a full circle setting on said sprinkler;

maintaining said established sprinkler height during both the disengaging of said arc adjustment section and during the moving of said arc adjustment section to said full circle setting.

39. (Newly Presented) A method according to claim 38, wherein moving the arc adjustment section to a full circle setting includes moving an adjustable arc stop out of a path of a direction changing switch.